

Cobra

Style and performance for cruisers, customs and tourers

- Aimed at the power cruiser/custom/touring market
- Incorporates sports tyre technology for nimble handling
- Special construction to deal with heavy loads
- Incredible stability and longevity - perfect for touring
- Unique 'snakeskin-effect' sidewall and aggressive tread pattern
- Extra wide sizes for custom bikes
- Original Equipment on the Triumph Bonneville Bobber
- Original Equipment on the Triumph Thunderbird LT
- Whitewalls available in some sizes



Cobra Technical Specifications

	size	load/spd index	rec rim (in)	alt rim (in) min/max	width (mm)	width (in)	dia (mm)	dia (in)	depth
Cobra AV71 (front)	80/90-21	48H	MT1.85	1.60-2.15	83	3.3	688	27.1	5.2
Cobra AV71 (front)	MH90-21	56V Reinforced	MT1.85	1.60 - 2.15	83	3.3	688	27.1	5.2
Cobra AV71 (front)	MH90-21 WW	56V Reinforced	MT1.85	1.60-2.15	83	3.3	688	27.1	5.2
Cobra AV71 (front)	90/90-21	54H	MT2.15	1.85-2.50	94	3.7	701	27.6	5.2
Cobra AV71 (front)	110/90-19	62H	MT2.50	2.15-3.00	119	4.7	682	26.9	5.2
Cobra AV71 (front)	100/90-19	57V	MT2.50	2.15-2.75	109	4.3	662	26.1	5.2
Cobra AV71 (front)	100/90-19 WW	57H	MT2.50	2.15-2.75	110	4.3	662	26.1	5.2
Cobra AV71 (front)	120/90-18	71H Reinforced	MT2.75	2.50-3.00	129	5.1	674	26.5	5.2
Cobra	120/70ZR19	(60W)	MT3.50	3.00-3.75	123	4.8	649	25.6	4.7
Cobra	120/70-21	68V Reinforced	MT3.50	2.75-3.75	120	4.7	709	27.9	4.8
Cobra	120/70-21 WW	68V Reinforced	MT3.50	2.75-3.75	120	4.7	709	27.9	4.8
Cobra AV71 (front)	MT90B16	74H Reinforced	3.00D	2.50-3.50	136	5.4	638	25.1	5.2
Cobra AV71 (front)	MT90B16 WW	74H Reinforced	3.00D	2.50-3.50	132	5.2	638	25.1	5.2
Cobra AV71 (front)	MT90B16 TRIKE	74H	MT3.00	2.50-3.50	133	5.2	638	25.1	4.7
Cobra (front)	130/60B19	61H	MT3.50	3.00 - 4.00	129	5.1	639	25.2	4.8
Cobra (front)	130/60B21	63H	MT3.50	3.00 - 4.00	129	5.1	689	27.1	4.8
Cobra AV71 (front)	130/80B17	65H	MT3.00	2.50 - 3.50	130	5.1	638	25.1	4.8
Cobra	130/70R18	63H	MT3.50	3.50-4.00	128	5.0	647	25.5	4.7
Cobra	130/70R18	63V	MT3.50	3.50-4.00	128	5.0	647	25.5	4.7
Cobra AV71	130/70B18	69H Reinforced	MT3.50	3.00-4.00	130	5.1	647	25.5	4.7
Cobra	140/75R17	67V	MT3.50	3.50-4.25	141	5.6	644	25.4	4.8
Cobra AV71 (front)	150/80-16	71H	MT3.50	3.00-4.25	157	6.2	637	25.1	5.2
Cobra	150/80R16	71V	MT3.50	3.50-4.25	149	5.9	646	25.4	4.7
Cobra	150/80R16 WW	71V	MT3.50	3.50-4.25	149	5.9	645	25.4	4.7
Cobra	150/80R17	72H	MT3.50	3.50-4.25	150	5.9	672	26.5	4.7
Cobra	150/80R17	72V	MT3.50	3.50-4.25	150	5.9	672	26.5	4.7
Cobra AV72	MT90B16	74H Reinforced	3.00D	2.50-3.50	133	5.2	638	25.1	8.7
Cobra AV72	MT90B16 WW	74H Reinforced	3.00D	2.50-3.50	133	5.2	638	25.1	8.7
Cobra AV72	140/90-15	76H Reinforced	MT3.50	2.75-3.75	149	5.9	633	24.9	8.7
Cobra AV72	140/90B16	77H Reinforced	MT3.50	2.75-3.75	143	5.6	649	25.6	8.7
Cobra AV72	140/90B16 WW	77H Reinforced	MT3.50	2.75-3.75	143	5.6	649	25.6	8.7
Cobra AV72	150/90B15	80H Reinforced	MT3.50	3.00-4.25	159	6.3	645	25.4	8.7
Cobra AV72	150/80B16	77V Reinforced	MT3.50	3.00-4.25	157	6.2	640	25.2	7.2
Cobra AV72	150/80B16 WW	77V Reinforced	MT3.50	3.00-4.25	157	6.2	640	25.2	7.2
Cobra	150/80R16	71V	MT3.50	3.00-4.25	152	6.0	646	25.4	8.0

	size	load/spd index	rec rim (in)	alt rim (in) min/max	width (mm)	width (in)	dia (mm)	dia (in)	depth
Cobra	150/80R16 WW	71V	MT3.50	3.00-4.25	154	6.1	646	25.4	8.0
Cobra AV72	150/70B18	76V	MT4.25	3.50-4.50	148	5.8	665	26.2	5.7
Cobra	160/70B17	79V Reinforced	MT4.50	3.75 - 5.00	161	6.3	656	25.8	8.7
Cobra AV72	160/80B16	81H Reinforced	MT3.75	3.00-4.50	167	6.6	665	26.2	8.7
Cobra AV72	170/80B15	83H Reinforced	MT4.00	3.00-4.50	176	6.9	659	25.9	8.7
Cobra	170/70R16	75H	MT4.50	4.50-5.00	170	6.7	645	25.4	8.2
Cobra	180/60R16	80H Reinforced	MT5.00	5.00-5.50	182	7.2	630	24.8	8.4
Cobra AV72	180/65B16	81H Reinforced	MT5.00	4.25 - 5.50	185	7.3	635	25.0	8.3
Cobra	18070R16	77H	MT5.00	5.00-5.50	182	7.2	656	25.8	8.5
Cobra	180/70R16 WW	77V	MT5.00	5.00-5.50	182	7.2	656	25.8	8.5
Cobra	180/55B18	80H Reinforced	MT5.50	5.50 - 6.00	178	7.0	655	25.8	8.7
Cobra	180/55ZR18	(74W)	MT5.50	5.50-6.00	184	7.2	655	25.8	6.6
Cobra	190/60R17	78H	MT5.00	5.00-6.00	190	7.5	663	26.1	6.8
Cobra	200/70-15	82H	MT5.50	4.75-6.25	211	8.3	665	26.2	7.7
Cobra	200/60VR16	(79V)	MT5.50	5.50-6.25	196	7.7	649	25.6	7.0
Cobra	200/55R17	78V	MT6.25	6.00-6.50	198	7.8	658	25.9	6.8
Cobra	200/55VR18	(79V)	MT6.25	6.00-6.50	198	7.8	679	26.7	6.8
Cobra	240/50R16	84V	MT7.50	7.00-8.00	237	9.3	649	25.6	7.2
Cobra	240/40VR18	(79V)	MT8.50	8.00-9.00	238	9.4	648	25.5	9.2
Cobra	250/40VR18	(81V)	MT9.00	8.50-9.50	251	9.9	655	25.8	6.6
Cobra	280/40VR20	(89V)	MT10.0	9.50-10.50	281	11.1	732	28.8	6.5
Cobra	300/35VR18	(87V)	MT10.5	10.00-11.00	300	11.8	664	26.1	6.5